

DBF-1668WW(100V)

¥4,800 ランプ別梱包

白色蛍光灯(GL)

本体/鋼板 白塗装

反射板/鋼板 白塗装

- ●消費効率:61.5ℓm/W(2950ℓm/48W) ●ランプ:FL40SW





ボルト穴 - 2-電源穴-

DCL-31422(100V)

¥4,400 ランプ別梱包

DCL-31424(200V)

¥5,700 ランプ別梱包





●消費効率:61.3ℓ m/W(2880ℓ m/47W)<31422> 61.3 & m/W(2820 & m/46W)< 31424 >

●ランプ: FL40SSW/37




DCL-31423(100V) DCL-31425(200V)

¥6,600 ランプ別梱包



本体/鋼板 白塗装



●消費効率:61.3ℓm/W(2880ℓm/47W)×31423> 61.3ℓm/W(2820ℓm/46W)×31425> ●ランプ:FL40SSW/37





DBF-1667WW(100V)

¥4,000 ランプ別梱包

20W×1灯 白色蛍光灯(GL)

本体/鋼板 白塗装 反射板/鋼板 白塗装

- 1 ∩kg
- ●片反射








¥5,000 ランプ別梱包

30W×1灯 白色蛍光灯(GL)

本体/鋼板 白塗装 ●1.0kg



| | | 端子台 2-取付ネジ穴 | 2-パイプ吊穴

¥6,200 ランプ別梱包 30W×1灯

白色蛍光灯(GH)










40W×2灯 高演色性昼白色蛍光灯(RS)

枠/鋼板 白塗装

反射板/鋼板 白塗装 ●消費効率:77.2ℓm/W(6250ℓm/81W) ●ランプ:FLR40SEX-N/M/36×2





300 x 1257

埋込穴





¥3,400 ランプ別梱包

20W×1灯 白色蛍光灯(GL)

本体/鋼板 白塗装 反射板/鋼板 白塗装

• 0.9kg ●笠付



20W×1灯 白色蛍光灯(GH)

本体/鋼板 白塗装 反射板/鋼板 白塗装

- 0.9kg ● 笠付





DBF-2985NW(100V) **DBF-2985LW**(100V)

¥6,000 ランプ付

本体/鋼板 白塗装

• 0.6kg

658-

電源穴

-取付\端子台





DBL-31461(100V) ¥11,000 ランプ別梱包

40W×1灯 高演色性昼白色蛍光灯(RH)

枠/鋼板 白塗装 反射板/鋼板 白塗装

●消費効率:75.5 ℓ m/W(3170 ℓ m/42W)電源穴 / 端子台





190 x 1257



D68-2886(100V)

¥3,200 ランプ別梱包

20W×1灯 白色蛍光灯(GL)

D68-2887(100V) ¥3,900 ランプ別梱包

白色蛍光灯(GH)





D68-2885(100V)

¥3,000 ランプ別梱包

10W×1灯 白色蛍光灯(GL)

本体/鋼板 白塗装 ●0.5kg





DBL-31460(100V) ¥11,000 ランプ別梱包

20W×2灯 昼白色蛍光灯(GL) 枠/鋼板 白塗装 反射板/鋼板 白塗装

300 × 639

埋込穴



¥6,100 ランプ別梱包

20W×1灯 昼白色蛍光灯(GL) 枠/鋼板 白塗装 反射板/鋼板 白塗装



190 x 639

