





**DBK-54159** (ホワイト)  
**DBK-54160** (メタリックシルバー)  
¥27,500 ランプ別 安定器別

- 70W (E26) × 1灯  
CDM-TP・拡散形
- 70W (E26) × 1灯  
セラメタ®・拡散形
- 本体 / 鋼板 塗装
- 反射板 / アルミ シルバーホーニング
- 強化ガラス 透明
- 2.1kg
- 安定器別置




**DBK-54157** (ホワイト)  
**DBK-54158** (メタリックシルバー)  
¥21,800 ランプ別 安定器別

- 70W (E26) × 1灯  
CDM-R (PAR30)
- 本体 / 鋼板 塗装
- パツフル / 鋼板 塗装
- 1.8kg
- 安定器別置



**DBK-54155** (ホワイト)  
**DBK-54156** (メタリックシルバー)  
¥21,800 ランプ別

- 75 ~ 150W (E26) × 1灯  
ビーム球
- 本体 / 鋼板 塗装
- パツフル / 鋼板 塗装
- 1.8kg



	CDM-TP (拡散形) 70W (E26)	
	3,000K	DP-54428 ¥13,300(5,800 ¥m 16,000h)
	8,500K	DP-54429 ¥13,300(5,800 ¥m 16,000h)
4,200K	DP-54430 ¥13,300(5,800 ¥m 16,000h)	

	セラメタ® (拡散形) 70W (E26)	
	3,000K	DP-54401 ¥14,300(6,500 ¥m 9,000h)
	8,500K	DP-54402 ¥14,300(6,500 ¥m 9,000h)
4,300K	DP-54403 ¥14,300(6,500 ¥m 9,000h)	


CDM-TP/セラメタ® 適合安定器  
インバータ  
70W用 DP-53271(100-242V) ¥23,000  
管灯回路配線長 2m以内

	CDM-R (PAR30) 70W (E26)	
	3,000K	狭角形 DP-54413 ¥14,000(68,000cd 9,000h)
		中角形 DP-54685 ¥14,000(13,500cd 9,000h)
		広角形 DP-54414 ¥14,000(10,000cd 9,000h)
4,200K	狭角形 DP-54415 ¥14,000(63,000cd 9,000h)	
	中角形 DP-54684 ¥14,000(13,000cd 9,000h)	
	広角形 DP-54416 ¥14,000(9,000cd 9,000h)	



CDM-R適合安定器  
インバータ  
70W用 DP-53271(100-242V) ¥23,000  
管灯回路配線長 2m以内  
4,200Kはインバータ専用です。

	ビーム球 (E26) [E750K]	
	集光	
	75W形	¥1,750(4,500cd 2,000h)
	100W形	¥1,800(7,000cd 2,000h)
	150W形	¥1,850(11,000cd 2,000h)
	散光	
75W形	¥1,750(1,800cd 2,000h)	
100W形	¥1,800(2,800cd 2,000h)	
150W形	¥1,850(4,200cd 2,000h)	

DBK-54159・54160



DBK-54157・54158



DBK-54155・54156

