














ハロゲン球 12V

100

12Vダイクロハロゲン球
50W(径50mm)

3,200K



照明率表 P.943-F-1

照明率表 P.943-F-2

照明率表 P.943-F-3



DDL-51854 (オフホワイト)

DDL-51855 (ブラック)

¥6,300 ランプ別 トランス別

50W(EZ10)×1灯
12Vダイクロハロゲン球(径50mm)

枠/銅板 塗装

- 0.4kg
- トランス別置
- 埋込必要高107mm
- 取付可能天井厚5-25mm

DDL-51858 (オフホワイト)


DDL-51859 (ブラック)

¥8,300 ランプ別 トランス別


50W(EZ10)×1灯
12Vダイクロハロゲン球(径50mm)

枠/銅板 塗装

- 0.4kg
- 首振り片側のみ45°・回転350°
- トランス別置
- 埋込必要高115mm
- 取付可能天井厚5-25mm



100
埋込穴



100
埋込穴



12Vダイクロハロゲン球(径50mm)50W(EZ10)3,200K
狭角形 DP-51862 ¥2,600(14,500cd 4,000h)
中角形 DP-51863 ¥2,600(4,800cd 4,000h)
広角形 DP-51864 ¥2,600(2,200cd 4,000h)
超広角形 DP-51998 ¥2,700(1,100cd 4,000h)



適合トランス
調光可能電子トランス
DP-36282(12V・75VA)¥3,500



適合トランス
低出力固定ロングラン調光可能電子トランス
DP-36283(12V・75VA)¥3,500

管灯回路配線長 1m以内